

Advanced Membrane Reactors in Energy Systems A Carbon-Free Conversion of Fossil Fuels

Investigators

ECN

Ruud W. van den Brink,	Senior Scientist (Dr) Catalytic Emission Reduction
Paul van Beurden,	Junior Scientist (Dr) Catalytic Emission Reduction
Rick T.J. Reijers,	Scientist (Dr) Catalytic Emission Reduction
Jean Pierre Pietersen,	Scientist (Dr) Catalytic Emission Reduction
Daniel Jansen,	Senior Scientist (Ir) Clean Fossil Fuels
Jan Wilco Dijkstra,	Scientist (Ir) Systems and Technology Assessments
Steven C.A. Kluiters,	Junior Scientist (Ir) Systems and Technology Assessments
Gonno P. Leendertse,	Senior Scientist (Ir) Technical Information Systems
Jaap F. Vente,	Scientist (Dr Ir) Molecular Separation Technology
Wim G. Haije,	Senior Scientist (Dr) Industrial Waste Heat Technology /Molecular Separation Technology

TU Delft

Joop Schoonman	Professor of Inorganic Chemistry
Cor J. Peters	Assistant professor Physical Chemistry and Molecular Thermodynamics

Introduction

A sustainable use of fossil fuels in the future will undoubtedly make use of concepts, where the energy content of the fossil fuel is first transferred to hydrogen, followed by the conversion to the desired energy form. The driving force for these concepts is the possibility of capturing CO₂ elegantly, while using the favorable thermodynamics to increase the efficiencies of fossil fuel conversion. We, ECN and TU-Delft, have identified membrane reactors as a game changing technology for highly efficient conversion of fossil fuels to carbon free energy carriers.

The purpose of this project is to develop hydrogen and CO₂ membranes to allow combination of natural gas reforming with H₂ or CO₂ separation in separation enhanced reactors, i.e. membrane reactors, for carbon-free hydrogen production or electricity generation. These devices offer multiple advantages, such as eliminating the requirement of water gas shift reactors with associated costs reductions; offering higher conversion efficiencies at lower temperatures; and decreasing primary energy use for CO₂ separation/capture associated with electricity generation.

Background

The steam reforming and the water gas shift equilibriums are key reactions for the production of hydrogen from fossil fuels:



By removing either CO₂ or hydrogen from the reaction mixture, the equilibrium can be shifted to the product side. Effectively, this can lower the reaction temperature and improve the purity of the product. In conventional, hydrogen production from natural gas, the steam-reforming step is followed by two water gas shift (WGS) reactors. When separating either CO₂ or hydrogen inside the reforming reactor, both the WGS steps can be eliminated. This implies that separation-enhanced techniques can also lead to investment costs reductions. Hydrogen or CO₂ separation is a flexible technique that can be used in hydrogen production from natural gas, but also can replace the WGS section of an IGCC or Biomass gasification plant. These techniques are especially suited for CO₂ capture, because the production of pure hydrogen and CO₂ streams is intrinsic to separation-enhanced reactors.

The combination of separation and reaction, as foreseen in membrane reactors, offers higher conversion of the reforming reactions at lower temperatures due to the removal of hydrogen or CO₂ from these equilibrium reactions, as shown in equations 1 and 2. For instance, in case natural gas reforming for carbon free hydrogen production, the use of membrane reactors will result in significantly lower operation temperatures (400 - 500°C) and higher efficiencies 85 - 90 instead of 75%. [1] In fact membrane reactors allow for low-irreversibility production and conversion of hydrogen to another energy form with integrated CO₂ capture.

Membrane reformers/reactors can be integrated in power generation systems but also in central heating devices. Our assessment studies clearly showed that in a more integrated approach of electricity production and CO₂ capture, using high-temperature membrane reactors will result in a substantially lower primary energy use for the CO₂ separation/capture [2]. Besides that, the low operation temperature of the membrane reactor creates possibilities for so-called chemical recuperation, compensating part of the CO₂ capture efficiency penalty.

Results

To date there have been no results to report since the formal contract between Stanford and ECN/TUD has not been signed yet. The only thing worth mentioning is that for all tasks a more detailed project plan has been written in close cooperation with the experts involved.

Progress

No progress since no work has been performed till now (see above)

Future Plans

See project plan and Statement of Work therein.

Publications

None

References

1. Bredesen, R., Jordal, K., Bolland, O., High temperature membranes in power generation with CO₂ capture, Chemical Engineering and processing, 43, 1129-1158, 2004

2. Lowe, C., CO2 capture Project: Pre-combustion technology Overview. Third Annual conference on Carbon Capture and sequestration, May 3- 6, 2004, Alexandria, Virginia USA

Contacts ECN

Daniel Jansen: jansen@ecn.nl

Wim G. Haije: haije@ecn.nl

TU-Delft

Joop Schoonman: j.schoonman@tnw.tudelft.nl

Cor J. Peters: C.J.Peters@tnw.tudelft.nl